

QuickFill SL Soft - 2K JOINT FILLER – SELF LEVELING

POLYUREA

1. Characteristic:

QuickFill SL Soft is a low viscosity and flexible 2-part, 100% solids Filler for Interior Control Joint Applications and Crack Repairs on concrete derived from a reaction of an Isocyanate and a Polyurea resin blend. This Self Leveling Material has been especially designed for interior horizontal applications requiring a slower set time. It is used for rapid installations in control joints and can be sprayed as a membrane for specific applications. It penetrates into fractures of joints preventing water intrusion and sub-base damage. It is an excellent maintenance tool and it seals against most fluids and other contaminants. After cutting it will produce a smooth surface that will extend the life of concrete and reduce maintenance expenditures.

2. Features:

- Meets USDA requirements, VOC free, 100% solids
- Self Leveling
- Immediate repair, drive over in 60 minutes
- Very high tensile and elongation
- Excellent Seal – Interior Control Joints – Joint Edge Support
- Stays flexible even in extreme cold conditions
- Not sensitive to moisture
- 100% Polyurea, low color change
- Resistant Chemicals Fuels, Oil and other contaminants
- Excellent abrasion- and high impact resistance

3. Typical Uses

- Cable Runs, Utility Cuts, Inductive Loops
- All Damages and Crack-Repairs on Concrete
- Control Joints, Interior concrete
- As slow set Spray Membrane
- Automobile and Aircraft Parking Zones
- Garage Decks, Concrete Docks
- Cold Storage Application
- Industrial Manufacturing Facilities
- 2K-Structure-Cement for special applications