



tradition • innovation • quality

a.b.e.® Construction Chemicals

# abe® durarroof

DO-IT-YOURSELF

## ACRYLIC ROOF PAINT WITH WATERPROOFING PROPERTIES



NON-TOXIC

**Suitable for cement, tiled or galvanised well drained roofs**



WATERPROOFING PROPERTIES

**Economical, tough, non-toxic, water based roof paint**



EXTERIOR

**Durable, weather resistant, good adhesion, waterproofing properties**



COVERAGE

**Theoretical spreading rate: 5 to 8 m²/L as a roof quote, 2 coats required.**

### USES

Roof paint suitable for cementitious, tiled or galvanised well drained roofs.

### ADVANTAGES

- Economical acrylic paint with waterproofing properties.
- Tough, non-toxic, water based paint for porous and non-porous surfaces.
- Offers durable, weather resistant and good adhesion on all prepared surfaces.
- Register for a 5 year quality guarantee (T&C's apply).
- Available in a range of standard roof colours with a smooth finish.

### COLOURS



### SURFACE PREPARATION

Ensure all surfaces are clean dry, sound and free from all laitance, fungal growth, grease, oil or loose and flaking particles.

### BONDING/PRIMING

All surfaces (except metal) – Dilute **abe® durarroof** with 10% clean water and prime total area to be covered. Allow to dry for ±30 minutes.

Metal surfaces only – Prime with **abe® 4-metal primer**. This not only gives excellent adhesion but resists rust. Allow to dry for 4 hours.

### MIXING

Stir well before use.

### COVERAGE

Spread rates are approximate subject to surface profile and porosity.

Recommended WFT: 163 microns per coat.

Theoretical spreading rate:

5 – 6 m² / L per coat on rough or absorbent surfaces.

7 – 8 m² / L per coat on smooth, non-porous surfaces.

### APPLICATION

All surfaces after priming: brush or roll on a 1st coat of **abe® durarroof** and allow to dry 2 – 3 hours.

Apply the 2nd coat of **abe® durarroof** and allow to hard dry for 24 hours.

Work roof sections downwards completing a tile or sheet at time.

Avoid lap marks by also keeping a wet edge during application.

Do not apply if rain is imminent.

### CLEANING

Tools must be cleaned immediately after use and before material has set with **abe® super brush cleaner** followed by washing with soap and water.

### PROTECTION ON COMPLETION

Whilst **abe® durarroof** is designed for an extended life, it is important to apply a maintenance coat of **abe® durarroof** every 3 years.

### PACKAGING

Available in 20 L containers.

Colours	Product Code	Bar code
Charcoal	22104-020	60020650 14002
Terracotta	22108-020	60020650 13968
Red	22107-020	60020650 14033
Grey	22106-020	60020650 14019
Green	22105-020	60020650 13982
Burgundy	22103-020	60020650 13975

WATERPROOFING

White 22101-020 60020650 14026

Available in 5 L containers.

Colours	Product Code	Bar code
Charcoal	22104-020-005	60020650 14002
Terracotta	22108-020-005	60020650 13968
Red	22107-020-005	60020650 14033
Grey	22106-020-005	60020650 14019
Green	22105-020-005	60020650 13982
Burgundy	22103-020-005	60020650 13975
White	22101-020-005	60020650 14026

#### IMPORTANT NOTE

This data sheet is issued as a guide to the use of the product(s) concerned. Whilst **a.b.e.® Construction Chemicals** endeavours to ensure that any advice, recommendation, specification or information is accurate and correct, the company cannot - because **a.b.e.®** has no direct or continuous control over where and how **a.b.e.®** products are applied - accept any liability either directly or indirectly arising from the use of **a.b.e.®** products, whether or not in accordance with any advice, specification, recommendation, or information given by the company.

#### FURTHER INFORMATION

Where other products are to be used in conjunction with this material, the relevant technical data sheets should be consulted to determine total requirements.

DATE UPDATED: 18/08/2022

**DATE UPDATED: 18/08/2022**

**a.b.e.®** is an ISO 9001:2015 registered company  
101 Main Reef Road, Boksburg North, 1459 | Tel: +27(0)11 306 9000  
**[www.abe.co.za](http://www.abe.co.za)**

