



SAINT-GOBAIN

abeproof acrylic primer

ACRYLIC WATER BASED PRIMER

DESCRIPTION

abeproof acrylic primer is a water based acrylic primer, sealer and bonding agent for the a.b.e.[®]proof liquid acrylic systems.

USES

abeproof acrylic primer is used as a primer, sealer and bonding agent to prepare surfaces prior to the application of waterproofing membrane and wall coating systems.

abeproof acrylic primer can be used to:

- Reduce dust and increase abrasion resistance of the substrate
- Act as a bonding agent to old torched membrane and acrylic waterproofing
- Prime and use as a bonding agent on smooth concrete finishes
- Seal pores on rough porous concrete to eliminate air bubbles
- For coating weathered bitumen

ADVANTAGES

- Easy to apply
- Water-based and non-toxic
- Excellent bonding capability

TYPICAL PHYSICAL PROPERTIES

Density	1.01 Kg/L
Flash Point	Non Flammable
Drying Time	30 min
Water Resistance	Very Good

Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

DATE UPDATED: 05/10/2023

a.b.e.[®] is an ISO 9001:2015 registered company
Call: (+27) 860 223 773 | (+27) 11 306 9000
www.abe.co.za

SURFACE PREPARATION

Ensure that surfaces are dry and clean and free from curing compounds or release agents. No chipping or roughening of surface is required provided the surface condition is stable. Old paintwork which is stable can remain. Any contamination including commercial detergents used for cleaning must be thoroughly rinsed off with plenty of water.

MIXING

Stir well before use.

COVERAGE

8 - 10 m²/L (1 coat)

APPLICATION

Apply **abeproof acrylic primer** to the clean substrate using a roller, brush or squeegee. Allow to dry before any subsequent applications are carried out. The primer is dry when all milkiness disappears.

CLEANING OF EQUIPMENT

Clean all brushes, rollers, trays, buckets and surrounding areas with clean water before the product sets **abe[®]super brush cleaner** may be used after setting.

PROTECTION/MAINTENANCE ON COMPLETION

Do not apply **abeproof acrylic primer** if rain is imminent.

MODEL SPECIFICATION

A water based acrylic primer

The priming system will be **abeproof acrylic primer**, a single-pack; acrylic compound applied in accordance with the recommendations of **a.b.e.[®]**

PACKAGING

abeproof acrylic primer is available in 20ℓ containers.

HANDLING & STORAGE

abeproof acrylic primer has a shelf life of at least 12 months when in original unopened container and stored in a cool dry place. Avoid freezing of the Primer.

HEALTH & SAFETY

Product safety information required for safe use is not included. Before handling, read product and safety data sheets and container labels for safe use, physical and health hazard information. The safety data sheet is available from your local **a.b.e.[®]** sales representative.

IMPORTANT NOTE

This data sheet is issued as a guide to the use of the product(s) concerned. Whilst **a.b.e.[®]** endeavours to ensure that any advice, recommendation, specification or information is accurate and correct, the company cannot accept any liability for application – because **a.b.e.[®]** has no direct or continuous control over where and how **a.b.e.[®]** products are applied.

FURTHER INFORMATION

Please consult our website for our latest datasheets.